



INVISISEAL IMPREGNATOR AI/31

Installation Instructions Sheet:

Read the Safety instructions on container, the Product Information sheet, Installation Instructions, and Safety Data Sheets No'd 31 before starting work.

InvisiSeal should not be diluted as it is supplied ready to use. Container should be shaken vigorously before opening and/or stirred thoroughly on opening.

Surface to be treated should be clean and dry and must be absorbent.

Apply with a brush or long haired roller or (not a foam roller). Alternatively an airless garden sprayer with a fan pattern nozzle can be used.

Apply an even, generous, coat sufficient to stay 'wet' for 5 – 10 mins and allow to penetrate surface. Any excess products must then be removed. Avoid runs, drips or puddles.

Tools can be cleaned in water.

CURING TIMES

Can be walked on after 60 mins and completely dry after 24 hours.

Any vehicular traffic should be kept off for 36 hrs - longer periods may be required in cooler weather conditions when used outdoors.

SUITABILITY

It is important that you test an area and leave to cure for at least 1 week to ensure the product is suitable for your requirements for overall appearance, performance, sheen/gloss and underfoot grip [slipperiness after sealing] - particularly important where the surface has previously been sealed. Please be aware if the surface has been sealed with a Polyurethane or water based sealer the old coating may require removal before applying a new coat of sealer.

CAUTION

Newly sealed surfaces can be slippery when first applied particularly where applying more than one coat.

Protect adjacent areas against splashes.

PACKAGING:

Available in 5ltr and 15ltr plastic containers.

DURABILITY

Indoors and lightly trafficked areas, with correct maintenance and depending upon surface type, potentially indefinite. Externally potentially 6 – 10 years, depending upon surface type.

MAINTENANCE

Sweep regularly to remove abrasive dirt and grit from surface and mop or hose daily using clean water. A mild detergent can be hand applied to heavy stains. Spills and marks should be wiped up/cleaned off and not allowed to dry on.

Adseal.info Unit 17-18 Raikes Clough Ind. Est. Bolton, BL3 1RP. Tel: 0845 026 2067 eMail: enquiries@adseal.info

This information is offered in good faith and is based upon data considered to be true and is offered for the users consideration, investigation and verification but no warranty is offered or implied based on the results obtained. Please read all attachments, recommendations or suggestions in conjunction with our conditions of sale which apply to all goods supplied by us in any form whatsoever. This product may be covered by patents or patents pending. Copyright 2010 T.D.S. Group Limited.
Printed in England